




450W Parking Lot LED light



Date:..... Location:

Product:..... Project:.....

Quantity:..... Catalog#

FEATURES

- Multiple mounts Available. slip filter, direct mount or yoke mounts
- 100-277V or 480V input voltage available. with 60121lm output.
- Robust profile housing with enhanced thermal heat sink.
- 6kV Built-in plus 10kV external surge protection
- 50,000hrs Life time.

SUITABLE APPLICATIONS

- Warehouses
- Stadiums
- Factories
- Parking Lots
- Shopping Malls
- Supermarkets
- Logistic Centers
- Auto dealerships

CONSTRUCTION:

Heavy die-cast aluminum alloy housing with bronze powder-coated finish.

OPTICAL SYSTEM:

High brightness lumileds LED chips.
Special PC lens with TYPE III and TYPE V distribution

ELECTRICAL:

Available as 120-277V or 480V input. -20°C to 45°C,

INSTALLATION&MOUNTING:

Slip filter, direct mounts or yoke mounts optional
for easy installation.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of
end-user environment application.

CONTROLS&DIMMING

0-10V dimming comes standard.

PERFORMANCE

Model NO	Wattage	Viewing Angle	Voltage/CurrentInput		Light Efficiency	Kelvin Options
			120V	277V		
LS-ESBV7E450WAT3A1-abcdefg	450W	Type III	3.75A	1.62A	133LM/W	30K/40K/50K

Model NO	Wattage	Viewing Angle	Voltage/CurrentInput		Light Efficiency	Kelvin Options
			347V	480V		
LS-ESBV7E450WAT3H1-abcdefg	450W	Type III	1.29A	0.93A	133LM/W	30K/40K/50K

Electric Characteristic

Specification/Model	LS-ESBV7E450WAT3A1-abcdefg	
LED Driver	UL listed LED DRIVER 0-10V Dimmable	
Input power	450W	450W
Lumens output	60121LM	60121LM
Efficiency	133LM/W	133LM/W
CRI	>82	>82
Color Temperature	5000K	5000K
Input voltage	120-277V/AC	277-480V/AC
Light distribution type	TYPE III	TYPE III
Working temperature	-20+45℃	-20+45℃
Junction temperature	<75℃	<75℃
lamps efficiency	≥90%	≥90%
Certificate	UL CUL DLC	UL CUL DLC
Equivalent	1000-1500W MH/HPS	1000-1500WMH/HPS

Electric Characteristic

PRODUCT ORDERING GUIDE

LS-ESBV7E450WAT3A1-abcdefg
1 2 3 4 5
[LS] - [ESBV7] E [450W] A [T3] [A1] abcdefg

- ☒ LS Factory code
- ☒ ESBV7 V7 Shoebox
- ☒ 450W Power ☒ T3 Light distribution type
- ☒ A1 Input voltage 120-277V/AC
- ☒ H1 Input voltage 277-480V/AC

Optional Mount Bracket:



AM Slipfitter Mount





DM Direct Mount



YM Yoke Mount


Optional Functions:

Photocell sensor options




Occupancy sensor options

► DIMENSION: Weight: 28lbs.





DISTRIBUTION DIAGRAM



► Installation

- 1.ADJUSTABLE FITTER MOUNTING (AM)
- Step 1:Loosen the four bolts on AM bracket, connect the wires correctly, and pull the wires into the poles.(Figure 1)
- Step 2: Place the bracket into the pole and lock the four bolts.(Figure 2)
- Notice: Adjustable angle is 0-90°(Figure 1)



2.DIRECT MOUNTING (DM)

Step 1: Fix DM bracket to square pole with bolt, open the side lid of DM bracket, pull the wire into junction box, and connect the wire correctly. (Figure 3)

Step 2: Put the connected wire into the junction box, then cover the junction box. (Figure 4)

Notice: Adjustable angle is 0-35° (Figure 3).

Same as round pole installation, please remember to remove the silicon plate when install the fixture in round pole (Figure 5)




Figure 3




Figure 4




Figure 5

3.YOKE MOUNTING (YM)

Step 1: Drill holes on the wall as shown. (Figure 6)

Step 2: Knock the expansion bolts into the wall. (Figure 7)

Step 3: Connect the fixture to the bracket and tighten the screws; connect the wires properly and put them into junction box. (Figure 8)

Notice: Adjustable angle is 0-90° (Figure 8)




Figure 6




Figure 7




Figure 8