

J Series

Explosion Proof Edge Lit LED Exit Light







Certifications:

- Marking UL844 (North American)
 - Class I, Division 1, Groups B, C, D
 - Olass I, Division 2, Groups A, B, C, D
 - Olass II, Division 1, Groups E, F, G
 - Olass II, Division 2, Groups F, G
 - Class III

- UL Marking
 - **O** UL924
 - **O** UL844
- UL 121201/CSA NO.213
- OSA C22.2 No.137-18
- Temperature Class (T-Rating)-T6

Standard Materials:

- Housing: A356T6 aluminum (less than .4% copper content) with baked-on gray epoxy finish
- Gasket: One-piece silicone
- Hardware: Stainless steel
- Mounting Sling: Stainless steel
- EXIT Sign: Tempered glass

IP66




J Series Explosion Proof Edge Lit LED Exit Light

Key Features:

- 1) Low energy consumption (3W/5W).
- 2 3-hour emergency operation.
- (3) Alternate exit legend and languages available.
- (4) Provided with 3/4 " NPT or M25 conduit hubs.
- (5) Long lifespan up to 50,000 hours.
- (6) Multiple installation options: wall mounting, pendant mounting, and pendant mounting with safe-wire.
- (7) Working temperature ranges from -40°F to 140°F.
- 8 5-year warranty.
- 9 Edge-lit sign

Ordering Guide:



- 1 Products for use in Harzardous Locations
 - EX- For all exit sign lights.

- 2 Lighting ystem input wattage rating 1W; 2W; 3W; 4W; 5W

- 4 Dimming feature opyion
 - N= Non-dimmable

- 5 LED color for LED lighting
 - G=Green color
 - R=Red color

- 6 BEAM ANGLE
 - **O** D180= 180°

Technical Data:

Model	Wattage	Operating Voltage	CRI	Color Temperature	Emergency Time
EX-3W JNGD180	3W(Max)	AC100-277V AC100-347V	>70	Red or Green	3 hours
EX-5W JNGD180	5W(Max)				

Packing Information:

Model	Quantity/Carton	Packing Size	Net Weight	Gross Weight
J	2 Pcs	18.50x18.50x10.24inch	13.23 lbs	30.86 lbs



J Series Explosion Proof Edge Lit LED Exit Light

