




J-B2B4B14®

FEATURES AND SPECIFICATIONS



Construction

- Integrative aluminum frame provides a durability structure
- 5 Wattage and 5 CCT selectable switches are integrated on the driver
- Minimize Stock, 1SKU can cover Max. of 25 Models

Electrical

- Input Voltage: 120-277Vac 50/60Hz
- 0-10V dimming
- THD ≤ 20%, PF ≥ 0.9

Applications

- Offices ,retail, Schools,restaurants, residential. and hospitality applications.

Installation

- Fixture is suitable for recessed mounting with T-bar, and accessories for suspension and surface mounting are also available. Use in ambient temperatures ranging from -20°C to 45°C

Listing

- ETL listed, suitable for damp location.
- DesignLights Consortium ®(DLC)Premium.

Warranty

- 5-year limited warranty

Specs at a Glance	* Nominal Wattage (Switchable)		
Configuration	J-B2-S40-3565-(blank,-S)	J-B4-S72-3565-(blank,-S)	J-B14-S40-3565-(blank,-S)
CCT (K)	3500K-4000K-5000K-5700K-6500K(Switchable)		
Wattage (W)	15W/20W/25W/ 30W/40W Wattage Adjustable	30W/40W/50W/ 60W/72W Wattage Adjustable	15W/20W/25W/ 30W/40W Wattage Adjustable
Lumens (lm)	1,950-5,000LM	3,900-9,000LM	1,950-5,000LM
Efficacy (LPW)	Up to 130		
CRI	≥ 80		
Input Voltage	120-277VAC, 50/60Hz, 0-10V Dimming		
Operating Temp	-20°C to 45°C		
Certifications	ETL DLC 5.1 Premium		
Warranty	5 Years		

BACKLIT PANEL LIGHT

 | JEELIGHTING

 Ordering information

Model	Description
J-B2-S40-3565-(blank,-S)	2' x 2' Backlit Panel, Power Switchable 15W/20W/25W/30W/40W, Color Switchable 3500K/4000K/5000K/5700K/6500K, Sensor Base
J-B4-S72-3565-(blank,-S)	2' x 4' Backlit Panel, Power Switchable 30W/40W/50W/60W/72W, Color Switchable 3500K/4000K/5000K/5700K/6500K, Sensor Base
J-B14-S40-3565-(blank,-S)	1' x 4' Backlit Panel, Power Switchable 15W/20W/25W/30W/40W, Color Switchable 3500K/4000K/5000K/5700K/6500K, Sensor Base

 Multiple Sensor Solutions



Model Number	Sensor Type	Controller	Controller
HD08VR-MB-1	Microwave	Audio Jack	Remote Control HD06R
HD08VR-MB-1	Microwave	Audio Jack	HAISEN BLUE APP
HD08VR-PB-1	PIR	Audio Jack	Remote Control HD06R
HD08VR-PB-1	PIR	Audio Jack	HAISEN BLUE APP


 Multiple Emergency Solutions



Emergency LED Driver
(HAISEN)

Emergency LED Driver,
9W, 90-Min Battery


Emergency LED Driver,
15W, 90-Min Battery



Flexible Installation Options


Cable Mount Kit

Optional Y cable mounting kit allows for suspended installations from any ceiling type. (2 pcs/kit)




Surface Mount Kit

Optional surface mount kit allows for installation on plaster or other hard ceilings.




Installation Instruction

Step1



Step2



Packing Information

Size/ft	L /inch	W /inch	H /inch	QTY/ctn	G.W./lbs	CTN QTY/pallet
2x2'	25.2	25.2	6.1	4	16.23	144pcs
2x4'	49.4	25.2	6.1	4	39.30	72pcs
1x4'	49.4	13.7	6.1	4	20.20	