



LED High Bay

# UFO-E

100W/150W/200W/240W





Chain

Hook

Wall Mounting  
(The U shaped bracket  
is an optional accessory)



UFO E series is designed by our sophisticated R&D team featuring high-efficiency, energy-saving and efficient heat-dissipation. The designing inspiration dated from diamond, which brought architectural aesthetics to this product. Due to its premium quality and excellent performance, UFO E series attained various international certifications. It is a perfectly ideal match for all kinds of applications involving warehouse, stadium, workshop, industrial plant, airport, railway station, etc.



# ▶▶▶ FEATURES

## ■ Emergency Back up Battery Available

Emergency time: 1.5 hours/3 hours

## ■ Smart Control

Built-in Motion Sensor

## ■ Power Adjustable

240W: Power can be adjusted to 240W, 200W, 150W

200W: Power can be adjusted to 200W, 150W, 100W

150W: Power can be adjusted to 150W, 100W, 80W

100W: Power can be adjusted to 100W, 180W, 50W

## ■ CCT Tunable

3000K/4000K/5000K Or 4000K/5000K/6000K

## ■ High Lumen Efficiency

Three options: 130lm/W, 170lm/W, 190lm/W


## ■ Energy Saving Up To 80-85%

Super bright and energy saving. Saving energy up to 80-85%, which can reduce electricity costs by 80%


## ■ Equipped With Reflector (OPTIONAL ACCESSORIES)

Improve lighting by up to 20% and reduce light loss

## ■ Compatible With Zhaga Socket (OPTIONAL)



Sensor Coverage



Power Adjustable



Sensor



6000K



5000K




4000K



3000K

# SPECIFICATION

	U-xxWE1 YZTXX	U-xxWE2 YZTXX	U-xxWE3 YZTXX
<b>Input Voltage</b>	AC100-277V/120-347V	AC100-277V/120-347V	AC100-277V/120-347V
<b>Power Consumption(±5%)</b>	100W; 100W(100/80/50W Adjustable)	150W(150/100/80W Adjustable)	200W(200/150/100W Adjustable); 240W(240/200/150W Adjustable)
<b>Power Factor</b>	0.95	0.95	0.95
<b>Driver</b>	VENAS Brand	VENAS Brand	VENAS Brand
<b>Intelligent Control</b>	0-10V Dimmable/DALI	0-10V Dimmable/DALI	0-10V Dimmable/DALI
<b>LED Chip</b>	2835	2835	2835
<b>Efficiency (±10%)</b>	130lm/W; 170lm/W/190lm/W	130lm/W; 170lm/W/190lm/W	130lm/W; 170lm/W/190lm/W
<b>CCT</b>	2700K-6500K	2700K-6500K	2700K-6500K
<b>CRI</b>	70/80	70/80	70/80
<b>Beam Angle</b>	60°/90°/120°	60°/90°/120°	60°/90°/120°
<b>IP Rating</b>	IP65	IP65	IP65
<b>IK Rating</b>	IK10	IK10	IK10
<b>Working Temperature</b>	-40°C(-40°F) - +50°C(122°F)	-40°C(-40°F) - +50°C(122°F)	-40°C(-40°F) - +50°C(122°F)
<b>Lifespan</b>	50,000 Hours	50,000 Hours	50,000 Hours
<b>Warranty</b>	5 Years	5 Years	5 Years
<b>Housing</b>	Die-cast Aluminum	Die-cast Aluminum	Die-cast Aluminum
<b>Lens Material</b>	Anti-UV PC Optical Material	Anti-UV PC Optical Material	Anti-UV PC Optical Material
<b>Net Weight</b>	2.1kg(4.6lbs)	2.6kg(5.7lbs)	3.6kg(7.9lbs)
<b>Gross Weight</b>	2.6kg(5.7lbs)	3.3kg(7.3lbs)	4.5kg(9.9lbs)
<b>Product Dimension</b>	Ø248x167mm(9.8x6.6inch)	Ø289x174mm(Ø11.4x6.9inch)	Ø336x191mm(Ø13.2x7.5inch)
<b>Packing Size</b>	294x294x180mm(11.6x11.6x7.1inch)	336x336x200mm(13.2x13.2x7.9inch)	387x387x210mm(15.2x15.2x8.3inch)




# ▶▶▶ ORDERING INFORMATION


U	xxW	Ei	Y	Z	T	X	X
UFO Light	Wattage 100W 150W 200W 240W	E Series Ei=E1	Y=N No Dimmable Y=D Dimmable	CCT 2700-6500K	T=D60, 60° T=D90, 90° T=D120, 120°	X=A, B Efficiency X=A 130lm/W X=B 170lm/W 190lm/W	X=277 100-277V X=347 120-347V

# ▶▶▶ PHOTOMETRIC DIAGRAMS


Specialized anti glare optical lens to deliver symmetric lighting solution  
60°/90°/120°




cd/klm



cd/klm



cd/klm





## APPLICATION AREAS

- Outdoor large sports arena
- warehouse
- Exhibition hall
- garage
- Outdoor football field
- Shipyard
- Sports center
- Stadium
- Logistics center
- factory



<END>

