



**Direct / Indirect Wall Mount
W60 Series
26 - 84W Compact Fluorescent**



Job Name: _____

Type: _____

Catalog Number: _____

Applications: Direct / Indirect Wall mounted fixture suitable for entry ways, walkways, perimeter, wall grazing and accent lighting. Wall mount to a height of 8'-15'.

Compact Fluorescent provides white light, energy savings and long life.

Dimensions: Height: 7-5/32", Width: 14-3/16", Extends from Wall: 6-13/16"

Catalog Number	Description	Volts	Total Watts	Lamp Life	Lamp Lumens	Lamp Base	Max Amps 120/208/240/277	Ballast Type
W60F26	26W CFL, Multi Tap	Universal	29	12,000	1,800	GX24q-3	.24 / .15 / .12 / .11	Electronic
W60F32	32W CFL, Multi Tap	Universal	36	12,000	2,400	GX24q-3	.31 / .21 / .17 / .13	Electronic
W60F42	42W CFL, Multi Tap	Universal	46	12,000	3,200	GX24q-4	.38 / .25 / .21 / .17	Electronic
W60F52	2x26W CFL, Multi Tap	Universal	55	12,000	3,600	GX24q-3	.46 / .29 / .25 / .21	Electronic
W60F64	2x32W CFL, Multi Tap	Universal	68	12,000	4,800	GX24q-3	.57 / .35 / .30 / .25	Electronic
W60F84	2x42W CFL, Multi Tap	Universal	93	12,000	6,400	GX24q-4	.78 / .47 / .40 / .33	Electronic

Specifications:

Housing: Heavy duty die cast aluminum housing. Includes easy hang wall mounting bracket for hands free wiring. Mounts over a 4" outlet box.

Lenses: Impact and thermal shock resistant clear soda lime glass.

Reflector: Aluminum reflector includes a removeable baffle to convert fixture from downlight to up/downlight.

Gasket: Housing and doors are sealed with a high temperature silicone gasket which seals out moisture and dirt.

Socket: Molded thermoplastic;
26W - 32W: 4-pin type, GX24q-3 Base
42W: 4-pin type, GX24q-4 Base

Ballast: Electronic High Power Factor (>.98)
Programmed Rapid Start, THD < 10%
Universal voltage, 120 through 277V 50/60Hz
Minimum starting temperature 0°F (-18° C)
End of lamp life shutdown protection

Lamp: Energy efficient Compact Fluorescent, included
26W - 32W: 4-pin type, GX24q-3 Base
42W: 4-pin type, GX24q-4 Base

Hardware: All hardware inside and outside the luminaire is nickel plated stainless steel.

Finish: Architectural Bronze. A nine step process of cleaning and treating the aluminum prepares it for powder coating. A durable polyester powder coat finish is then applied ensuring a long lasting finish.

Photocell: Specify **PC1** for 120V and **PC2** for 208-277V. Field Installed.

Approvals: CSA (c & us) Listed. Suitable for Wet Locations

Note: 1- Specifications may change without notice.
2. Lamp Life and Lumens listed are initial values and are affected by lamp orientation and operating conditions.




**Direct / Indirect Wall Mount
W60 Series
26 - 84W Compact Fluorescent**



The chart is based on a W60 mounted 10' above the ground. Each iso-line represents the footcandle level along the path. Each square represents the mounting height. To change the height of the fixture or to change the wattage use the multipliers below.

W60F84 - 84W Compact Fluorescent - Downlight Portion only



Mounting Height	Multiplier	Watts CFL	Multiplier
10'	1	26	.28
12'	.69	32	.38
15'	.44	42	.5
18'	.31	52	.56
		64	.75
		84	1